



Enterprise-Ready Network Security Solution Overview

The nAppliance mISAE 2100B is an enterprise grade integrated edge gateway security appliance based on an embedded version of Microsoft Forefront Internet Security and Acceleration (ISA) Server 2006 Enterprise Branch Edition. It delivers comprehensive, multi-layered defense against threats to networks and Microsoft applications, content acceleration, intuitive management, and scalability - fully integrated, easy to deploy at branch office with turnkey "out of the box" convenience which includes

Unified Gateway Security Solution: One platform which fits all business security needs. Purpose-built, robust, multi-purpose standalone security and content caching solution for small offices to large enterprise deployments, provides single sign-on and seamless Active Directory Service Integration. Support large number of 3rd party ISV add-on security software modules.

Simplified – Branch Office Site-Site Infrastructure, Efficient Management: Centralized CSS management of firewall, VPN, and cache security policies provides unattended branch-office manageability, and branch office deployment automation makes large scale roll-outs a snap.

Secure Web Application Publishing Solution: Securely publish Exchange, OWA, SharePoint or any web application for remote access. Securely extend access to partners, customers, consultants and remote employees to applications, documents, and data from any PC or device from outside the corporate network.

Anywhere VPN Remote Access Solution: Securely extend access to partners, customers, consultants and remote employees to applications, documents, and data from any PC or device from outside the corporate network.

Web Content Filtering Solution: Employee web access control and protection.

nAppliance Platform Highlights

The nAppliance mISAE 2100B is ideal for Medium to Large Size Branch deployments; it's a purpose-built, 1U rack-optimized and most competitive security solutions appliance platform in its class. It provides

- Powered by Intel Xeon Quad Core Processor, its unique architecture offers high performance multi-core Processing, a large 8MB high-speed cache, multi-lane PCIe bandwidth, virtualization, deep packet acceleration with lowest packet latency, highest system throughput and unfaltering scalability to support large number of processor intensive integrated security applications workload.
- Ease of installation and configuration flexibility, the appliance provides Six Gigabit Ethernet RJ-45 ports and can be deployed in as little as 30 minutes.
- Built-in SSL/IPSec Crypto Offload Accelerator offers highest application performance and network throughput.
- Ease of System Administration thru LCD Manager and FFRS, a Flash based Field Restore System and Image automation tool. Front-panel Graphical LCD interface helps ease appliance setup and system status checkups. FFRS enables system image backup, restore and "Bare-Metal" recovery. Backup any number of system image to local disk partition, removable media or a network target, such images than can be used for a quick restore to "last good known state". Bare-Metal appliance recovery support, restore a "factory-default" image from a secondary hard disk partition or a Recovery DVD media.
- Maximum uptime thru superior thermal design, system reliability, component-level redundancy, serviceability and built-in remote lights-out appliance system hardware manageability option. Hardware RAID controller and dual disk drive mirroring configuration allows uninterrupted system operations in case of a single disk drive failure, redundant hot-swap disk drives offers highest level of availability and no downtime while RAID array is being rebuilt on replacement drive. Industry standard IPMI based Out-Of-Band, lights-out manageability for BIOS-level remote system access; IPMI operates independent of the operating system, when sending commands to the appliance hardware over IP network, it provides administrators remote access with the ability to monitor, manage, receive alerts, diagnose and recover appliance systems, even if the operating system has hung or the system is powered down.
- System high availability thru Microsoft network load balancing (NLB) clustering array support, supports up to 2 nodes.
- Extensible support for optional 3rd-party ISV applications. Optional modules are pre-tested and pre-packaged for a true multi-functional security solution experience, easy one click field install, maintenance and help Future-proof your network with functionalities such as bandwidth management, web content filtering, spam filtering, anti-phishing, anti-virus, IM filtering, End Point NAC Security, VoIP, and Terminal Printing.

Solution Key-Features

- Enhanced "Integrated Edge Security" gateway architecture, supports industry standards and seamless integration into Microsoft centric infrastructures and offers centralized policy based access control tied to Active Directory
- Microsoft ISA Server Enterprise Branch 2006 Standard and Hardened Windows Server 2003
- System Scalability and High Availability, up to 2 NLB nodes cluster
- Application-Layer Firewall Support
- VPN Client Support
- Branch Office Site-Site connectivity, centralized management and large scale deployment automation
- Secure Web Application Publishing
- Web Cache and Bandwidth Optimization for accelerated content delivery
- Easy Windows MMC based Manageability
- Bandwidth Management (QoS) support thru FairShare

Net-Gateway mISAE Enterprise Series

Product Datasheet: mISAE 2100B

- Centralized Appliance System Management thru nAppliance ONEface™ Web Manager
- LCD based Appliance Configuration thru nAppliance LCD Manager
- Field Backup, Restore and “Bare-Metal” Recovery thru nAppliance FFRS™ System
- “Best of Breed” support for leading 3rd party security software applications options from Websense, McAfee, Kaspersky, Secure Computing, RSA, Winfrasoft, Burstek, GFI, Collective Software and Avira
- Superior Future-Proof Product built on Microsoft Edge Forefront Technology
- Support option includes Advance Hardware Replacement and Multiple Levels of Help Desk Support
- Lowest Total Cost of Ownership

Appliance Performance:

- Deployment Type: ⇒ Medium to Large Size Branch
- Recommended Corporate PCs: ⇒ 2,000
- Recommended Corporate Web Users: ⇒ 10,000
- Firewall Throughput (Mbps): ⇒ 2,400
- HTTP Throughput (Mbps): ⇒ 200
- VPN Throughput (Mbps): ⇒ 200
- SSL/IPSec Accelerator Rating (TPS): ⇒ 17,000 (max)
- SSL/IPSec Rating Accelerator (Throughput): ⇒ 2.5Gbps (max)
- TMG Optimized: ⇒ Yes

Hardware Specifications:

- LAN Ports (PCIe): ⇒ 6-GbE
- CPU: ⇒ 1x Intel Xeon Quad Core
- CPU Processing Cores: ⇒ 4 w/8MB Cache
- System Memory: ⇒ 6 GB DDR2 ECC (earlier models w/4GB)
- SSL/IPSec Hardware Acceleration: ⇒ Yes
- Hard Disks: ⇒ 2 x 500 GB, SATA2, Hotswap (earlier model w/250GB)
- Hard Disk Redundancy: ⇒ Yes, RAID-1 Mirroring
- Flash Disk (Recovery OS): ⇒ Yes
- LCD Interface w/6-Keypad: ⇒ Yes, Graphical
- Remote (Out of Band) Appliance HW Management: ⇒ Yes
- ROM (CD/DVD): ⇒ Yes
- Power Supply: ⇒ Single, 560 Watts. 100-240 AC Auto Sensing
- Power Redundancy: ⇒ No
- IO Ports (USB / RS232 / VGA): ⇒ 2 / 1 / 1
- Form Factor: ⇒ 1U, 4-Post Rack (rails incl)
- Dimensions (H x W x D): ⇒ 1.75 x 17 x 25 (inch)

Appliance Integrated Appliance “Turnkey” Solutions

Network Edge Security is a critical business function. Trust nAppliance to deliver reliable and comprehensive solutions. nAppliance is an ISO 9001:2000 certified manufacturer. The nAppliance Net-Gateway mISAE appliances are engineered and manufactured to exacting quality specifications. The mISAE product line is one of a family of integrated network security and application acceleration appliances.



nAppliance Networks, Inc.

540 Dado Street, San Jose, CA 95131, USA

Phone: 1-408-895-5000 (Local) 1-877-895-nAPP (6277) (US-Toll Free) 011-408-895-5000 (International)

Fax: 1-408-943-8222/8101 **Email:** info@nappliance.com **Website:** <http://www.nappliance.com>



nAppliance Networks, the nAppliance Networks, mISA, mISAE, mIAG, ONEface, FFRS are trademarks of nAppliance Networks, Inc. All other brands, product names, trade names, trademarks and service marks used herein are the property of their respective owners. Copyright ©2006 nAppliance Networks, Inc. All rights reserved.

** (09/21/2009), TMG Enhanced platforms includes additional RAM and larger size hard disks. Models 2100 and above, requires TMG upgrade w/Windows 2008R2 support to utilize memory size larger than 4GB.